


Glazing Bead Saw

Glazing Bead Saw designed for 90° cutting of 2 aluminium or uPVC glazing beads in one clamping - suitable for plants of any size

GLA 404



Characteristic features:

- Simultaneous cutting of 2 glazing beads
- Variable hydropneumatic saw blade feed
- Saw blades are arranged at the top
- Universal bead clamping on the fixing area applicable for all glazing beads of the same basic geometry
- Pre-adjustment of the glazing bead's inclination by hand wheel and spindle for an optimal assembly of the glazing beads in proportion to the glass thickness
- Spraying device (ALU)

Optional extras:

- Manual, digital and/or electronic length stop systems with PC control
- Clamping system for glazing beads without fixing area
- Preparation for the installation of an extraction unit
- Extraction unit

Technical data:

- Power (kW): 1,1
- Voltage (V): 400
- Compressed air (bar): 7
- Air consumption (l/working cycle): approx. 15
- Saw blade Ø (mm): 250
- Max. profile cross section (mm):
50 x 50 (with retaining foot clamping)
37,5 x 45 (without retaining foot clamping)
- Min. cut length (mm):
200 (without length stop)
260 (with ROTOX length stop)
- Machine dimensions W x D x H (mm):
700 x 1.350 x 1.250
- Weight (kg): 220
- Workable material:
aluminium and uPVC glazing beads